






Mid Modules & Connectors

Standard 8" Profile



DYNAMIC CONVEYOR CORPORATION

Fill in __ with 04, 06, 08, 10, 12, 14, 16, 18, 20, 22, 24, 26, 28, 30, 36, 42, 48, 54 or 60 for conveyor width

Modules / Connectors	Part Number	Functions / Features / Construction
17-1/2" Straight Extension 	EDNX__	<ul style="list-style-type: none"> • Connect between feed and drive modules to extend by 17-1/2" • Requires 3' of belt
6-1/2" Straight Connector 	JSNX__	<ul style="list-style-type: none"> • A straight connector will connect with another straight, 30° or 45° angle • Requires 1' of belt
30° Angle Connector 	JTNX__	<ul style="list-style-type: none"> • Use angles to change elevation (ascending or descending) • Use a combination of angle connectors to achieve angles of various degrees • Requires 1' of belt
45° Angle Connector 	JFNX__	<ul style="list-style-type: none"> • Use angles to change elevation (ascending or descending) • Use a combination of angle connectors to achieve angles of various degrees • Requires 1' of belt
Standard Radius Turn Modules 	R__ -45 R__ -90 "Special"	<ul style="list-style-type: none"> • Standard profile height (8") • Available in 4", 6", 8", 10", 12", 18", 24" widths • Available in 45° and 90° radius turns • Connect between two modules to allow the conveyor to turn right or left at a given angle • Use with External Mount Radius Turn Drive Module • Requires Straight Extension Module(s) before changing direction (right or left) • Requires Series 2400 Radius Flush Grid Belt • Reversing options not available