







Drive & Feed End Modules

Standard 8" Profile



DYNAMIC CONVEYOR CORPORATION

Fill in __ with 04, 06, 08, 10, 12, 14, 16, 18, 20, 22, 24, 26, 28, 30, 36, 42, 48, 54 or 60 for conveyor width

Drive Modules	Options	Ref. Number	Functions / Features / Construction
 <p>External Mount Motor and Control</p>	<p>Variable Speed</p> <p>1/2 - 26 FPM 1 - 47 FPM 2 - 78 FPM</p>	<p>HDV__E</p> <p>Specific part number will be configured during the quoting phase.</p>	<ul style="list-style-type: none"> Available for all widths 110 VAC single phase, 230 VAC single phase or 230 three phase Lockable speed control Brushless Stainless steel shaft Required for water applications Requires 3' of belt
 <p>Internal Mount Motor</p>	<p>Variable Speed</p> <p>1/2 - 26 FPM 1 - 47 FPM 2 - 78 FPM</p>	<p>HDV__I</p> <p>Specific part number will be configured during the quoting phase.</p>	<ul style="list-style-type: none"> Available for widths 10" or more 110 VAC single phase, 230 VAC single phase or 230 three phase Lockable speed control Brushless Stainless steel shaft Required for water applications Requires 3' of belt
 <p>External Mount AC Variable Frequency Motor</p>	<p>Variable Speed</p> <p>1/8HP - 11 FPM 1/4HP - 35 FPM 1/2HP - 70 FPM</p>	<p>HDV__EVFD</p> <p>Specific part number will be configured during the quoting phase.</p>	<ul style="list-style-type: none"> Available for all widths 110/60/1ph, 230/60/1ph or 460/60/3ph 500 in lb/155 torque Brushless Stainless steel shaft Requires 3' of belt
 <p>External Mount Radius Turn Motor</p>	<p>Variable Speed</p> <p>1/8HP - 11 FPM 1/4HP - 35 FPM 1/2HP - 70 FPM</p>	<p>RTVS__E</p> <p>Specific part number will be configured during the quoting phase.</p>	<ul style="list-style-type: none"> Available for radius turn conveyors Brushless Stainless steel shaft Requires 3' belt Indexing and reversing options not available
Feed End Modules	Options	Part Number	Functions / Features / Construction
 <p>Feed End Module</p>		TENX__	<ul style="list-style-type: none"> Begins the return end of a conveyor system Required in all systems Requires 4' of belt
 <p>Heavy Duty Feed End Module</p>		TENX__-HD	<ul style="list-style-type: none"> Typically used on conveyors that require more than 100 square feet of belting External adjustment mechanism Requires 4' of belt